



SAFETY DATA SHEET

Version 3.0 Revision Date 09/04/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name

: Tantalum

Brand

: SAM

CAS-No.

: 7440-25-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Stanford Advanced

Company

: Materials

23661 Birtcher Dr.

Lake Forest, CA 92630

USA

Telephone

+1 (949) 407-8904

Fax

+1 (949) 812-6690

1.4 Emergency telephone number

Emergency Phone #

+1 (949) 407-8904

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable solids (Category 2), H228

Skin irritation (Category 2), H315

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H228 Flammable solid. H315 Causes skin irritation.

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove P305 + P351 + P338 contact lenses, if present and easy to do. Continue rinsing. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.

2.3Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1Substances

Formula

Та

Molecular weight CAS-No.

: 180.95 g/mol : 7440-25-7

Hazardous components

Component	Classification	Concentration
Tantalum powder		
	Flam. Sol. 2; Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; H228,	90 - 100 %
	H315, H319, H335	

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL

PROTECTION 8.1 Control parameters

Components with workplace control parameters

Components with workplace control parameters				
Component	CAS-No.	Value	Control	Basis
			parameters	
Tantalum powder	7440-25-7	TWA	5.000000	USA. Occupational Exposure Limits
			mg/m3	(OSHA) - Table Z-1 Limits for Air
				Contaminants
		TWA	5.000000	USA. ACGIH Threshold Limit Values
		: .	mg/m3	(TLV)
	Remarks	Upper Respiratory Tract irritation		
		Adopted values or notations enclosed are those for which changes		

			are proposed in the NIC See Notice of Intended Changes (NIC)		
			TWA.	5.000000	USA. NIOSH Recommended
. '				mg/m3	Exposure Limits
			ST	10.000000	USA. NIOSH Recommended
				mg/m3	Exposure Limits
			TWA	5.000000	USA. NIOSH Recommended
	:	1	: ' '	mg/m3	Exposure Limits
			ST	10.000000	USA. NIOSH Recommended
				mg/m3	Exposure Limits
1			TWA	5.000000	USA. NIOSH Recommended
				mg/m3	Exposure Limits
			ST	10.000000	USA. NIOSH Recommended
:				mg/m3	Exposure Limits
			TWA	5 mg/m3	USA. NIOSH Recommended
					Exposure Limits
			ST	10 mg/m3	USA. NIOSH Recommended
				1	Exposure Limits
			PEL	5 mg/m3	California permissible exposure
					limits for chemical contaminants
					(Title 8, Article 107)

8.2Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with glove's. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: powder

Colour: light grey

b) Odour No data available

c) Odour Threshold No data available

d) pH No data available

e) Melting point/freezing Melting point/range: 2,996 °C (5,425 °F)

point

f) Initial boiling point and boiling range

5,425 °C (9,797 °F)

g) Flash point

Not applicable

h) Evaporation rate

No data available

i) Flammability (solid, gas)

The substance or mixture is a flammable solid with the category 2.

j) Upper/lower

,

No data available

flammability or explosive limits

k) Vapour pressure

No data available

I) Vapour density

No data available

m) Relative density

16.69 g/cm3

n) Water solubility

insoluble

o) Partition coefficient: n-

No data available

octanol/water

p) Auto-ignition temperature

300 °C (572 °F)

q) Decomposition temperature

No data available

r) Viscosity

No data available

s) Explosive properties

No data available

t) Oxidizing properties

No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Tantalum Oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LC50 Oral - Mouse - 595 mg/kg

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC:

No component of this product present at levels greater than or equal to 0.1% is identified

as probable, possible or confirmed human carcinogen by IARC.

NTP:

No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP.

OSHA:

No component of this product present at levels greater than or equal to 0.1% is identified as

a carcinogen or potential carcinogen by OSHA...

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3089 Class: 4.1 Packing group: II

Proper shipping name: Metal powders, flammable, n.o.s.

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 3089 Class: 4.1 Packing group: II

EMS-No: F-G, S-G

Proper shipping name: METAL POWDER, FLAMMABLE, N.O.S.

IATA

UN number: 3089 Class: 4.1 Packing group: II

Proper shipping name: Metal powder, flammable, n.o.s.

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

Massachusetts Right To Know Components

CAS-No. **Revision Date** 7440-25-7 1993-04-24 Tantalum powder

Pennsylvania Right To Know Components

CAS-No. **Revision Date** Tantalum powder 7440-25-7 1993-04-24

New Jersey Right To Know Components

CAS-No. **Revision Date** 7440-25-7 1993-04-24 Tantalum powder

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eve Irrit. Eye irritation Flam. Sol. Flammable solids Flammable solid. H228 H315 Causes skin irritation.

H319 Causes serious eye irritation. May cause respiratory irritation. H335

Skin Irrit. Skin irritation

STOT SE Specific target organ toxicity - single exposure

3

HMIS Rating

Health hazard: 2

Chronic Health Hazard:

Flammability:

Page 7 of 8

Physical Hazard		3
-----------------	--	---

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 3

Further information

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.