

samaterials.com

SAFETY DATA SHEET

Version 3.0 Revision Date 09/04/2017

1. P	RODUCT AND COMPANY	IDENTIFICATION	1	1 1 1		1			
1.1	Product identifiers								
¹	Product name Brand	: Copper : SAM			¹	}		1.1	
	CAS-No.	: 7440-50-8							
1.2	Relevant identified uses of	the substance or mixture a	nd uses advis	ed against					
	Identified uses	: Laboratory chemicals	, Synthesis of s	ubstances					
1.3	Details of the supplier of th	ne safety data sheet					: ' '	111	
'	Company	Stanford Advanced Materials 23661 Birtcher Dr. Lake Forest, CA 926	530		*	1	1 - 1 1		;
	Telephone Fax	USA : +1 (949) 407-8904 : +1 (949) 812-6690				÷			
1.4	Emergency telephone num	iber i i i i i i i i i i i i i i i i i i i							
	Emergency Phone #	: +1-(949) 407-8904							
2. H	IAZARDS IDENTIFICATION								
2.1	Classification of the subs	tance or mixture							
	GHS Classification in acc Flammable solids (Categor Acute aquatic toxicity (Cate Chronic aquatic toxicity (Ca	gory 1), H400	(OSHA HCS)			:			÷
	For the full text of the H-Sta	atements mentioned in this S	Section, see Se	ection 16.			: • •		
2.2	GHS Label elements, inclue	ding precautionary stateme	nts						
*	Pictogram				'				
	Signal word Hazard statement(s)	Danger		· · ·		ť			;
	H228 H400	Flammable solid. Very toxic to aquatic	life						
	H228 H400 H412	Flammable solid. Very toxic to aquatic Harmful to aquatic li		sting effects	6.				
	H400	Very toxic to aquatic Harmful to aquatic li	fe with long las		. 11	es. No smo	king.		• •
	H400 H412 Precautionary statement P210 P240 P241 P273	Very toxic to aquatic Harmful to aquatic li (s) Keep away from hea Ground/bond contain Use explosion-proof Avoid release to the	fe with long las at/sparks/open her and receivi electrical/ ven environment.	flames/hot ing equipm tilating/ ligh	surface ent. nting/ ec	luipment.	king.		· : :
	H400 H412 Precautionary statement P210 P240 P241	Very toxic to aquatic Harmful to aquatic li (s) Keep away from hea Ground/bond contain Use explosion-proof	fe with long las at/sparks/open ner and receivi electrical/ ven environment. ves/ eye protec	flames/hot ng equipm tilating/ ligh	surface ent. nting/ ec	luipment.			

2.3Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1Substances

Formula	: Cu
Molecular weight	: 63.55 g/mol
CAS-No.	: 7440-50-8
EC-No.	: 231-159-6
	1

Hazardous components

Component				Classification	Concentration
Copper					
		i.	i.	Flam. Sol. 1; Aquatic Acute 1; Aquatic Chronic 3; H228, H400, H412	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL

PROTECTION 8.1 Control parameters

Components with workplace control parameters

Compone	nt	CAS-No.	Value	Control parameters	Basis
Copper		7440-50-8	TWA	1.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	1 - 1 1	Remarks	Irritation Gastrointes metal fume		
			TWA	1.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
			TWA	1.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
			TWA	0.200000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
			Irritation Gastrointes metal fume		

				TWA	0.100000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	1			TWA	1.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
				Irritation Gastrointe metal fume	stinal	
				TWA	0.200000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
				Irritation Gastrointe metal fume		
1	н н 1		1	TWA	1.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
				TWA	1.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
				TWA	1.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		'		TWA	1.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
				TWA	0.100000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
1				TWA	1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
				Irritation Gastrointe metal fume		
				TWA	0.2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
				Irritation Gastrointe metal fume		
	1			TWA	1 mg/m3	USA. NIOSH Recommended Exposure Limits
				TWA	1 mg/m3	USA. NIOSH Recommended Exposure Limits
				TWA	1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
				TWA	0.1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
:			1	PEL	0.1 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder Colour: light red							
b)	Odour	No data available						: * *	
c)	Odour Threshold	No data available							
d)	рН	No data available							
e)	Melting point/freezing point	Melting point/range:							
f) [†]	Initial boiling point and boiling range	2,567 °C (4,653 °F)	- lit.						:
g)	Flash point	No data available							
h)	Evaporation rate	No data available			111			: • •	
i)	Flammability (solid, gas)	The substance or m	ixture is	a flammabl	e solid w	ith the ca	tegory 1.		
j)	Upper/lower flammability or explosive limits	No data available							
k)	Vapour pressure	No data available							
I)	Vapour density	No data available							
m)	Relative density	8.94 g/mL at 25 °C	(77 °F)						

. * *	,						. * *				
'	n)	Water solubility	No data avai	ahle	:						1
	o)	Partition coefficient: n- octanol/water	No data avai								
	p)	Auto-ignition temperature	No data avail	able							
. • •	q)	Decomposition temperature	No data avai	able					:**		
	r)	Viscosity	No data avai	able							
•••	s)	Explosive properties	No data avai	able						· · · ·	
	t)	Oxidizing properties	No data avai	able							
.2		safety information ata available			:			:			÷
10.	STAB	ILITY AND REACTIVITY									
0.1	Reac No da	tivity ata available				111			111		
0.2	Stabl	lical stability e under recommended st	-	S.	:		*	-			
).3	No da	bility of hazardous react ata available	ions		:			:			i.
0.4	Heat,	i tions to avoid flames and sparks.									
0.5		n patible materials g acids, Strong oxidizing	agents, Acid ch	lorides, Hal	ogens				111		
0.6	Haza Other	rdous decomposition p rdous decomposition pro decomposition products e event of fire: see sectior	ducts formed ur - No data avail		ditions C	copper oxid	es	:			1
11.	τοχια	OLOGICAL INFORMAT	ION	·			.'			.'	
11.1	1 Info	ormation on toxicologica	l effects								
		ute toxicity ata available									
	Inhala	ation: No data available									
	Derm	al: No data available									:
	LD50	Intraperitoneal - Mouse	- 3.5 mg/kg								
		corrosion/irritation rritate skin.	: :		:	1 - 1 1		e la compañía de la c			÷
		ous eye damage/eye irri rritate eyes.	tation								
		iratory or skin sensitis a ata available	ation						111		
'		n cell mutagenicity ata available		·			'				
	Ca	rcinogenicity									
. 1	IAF	RC: No component as probable, po					ual to 0	.1% is idei	ntified		1
	NT	P: No component o	f this product pre	esent at leve	ls greater th	nan or equal	to 0.1%	is identifie	d as a		
										Page 6	of 0

known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. **Reproductive toxicity** No data available No data available Specific target organ toxicity - single exposure May cause respiratory irritation. Specific target organ toxicity - repeated exposure No data available Aspiration hazard No data available Additional Information RTECS: GL5325000 Symptoms of systemic copper poisoning may include: capillary damage, headache, cold sweat, weak pulse, and kidney and liver damage, central nervous system excitation followed by depression, jaundice, convulsions, paralysis, and coma. Death may occur from shock or renal failure. Chronic copper poisoning is typified by hepatic cirrhosis, brain damage and demyelination, kidney defects, and copper deposition in the cornea as exemplified by humans with Wilson's disease. It has also been reported that copper poisoning has lead to hemolytic anemia and accelerates arteriosclerosis., Damage to the lungs., Vomiting, Diarrhoea, Abdominal pain, Blood disorders Liver - Irregularities - Based on Human Evidence Liver - Irregularities - Based on Human Evidence **12. ECOLOGICAL INFORMATION** 12.1 Toxicity Toxicity to fish mortality LOEC - Oncorhynchus mykiss (rainbow trout) - 0.022 mg/l - 96 h Toxicity to daphnia mortality NOEC - Daphnia (water flea) - 0.004 mg/l - 24 h and other aduatic invertebrates EC50 - Daphnia magna (Water flea) - 0.04 - 0.05 mg/l - 48 h 12.2 Persistence and degradability Biodegradability Result: - Readily biodegradable. 12.3 Bioaccumulative potential Cyprinus carpio (Carp) - 40 d Bioaccumulation - 200 mg/l Bioconcentration factor (BCF): 108 Mobility in soil 12.4 No data available Results of PBT and vPvB assessment 12.5 PBT/vPvB assessment not available as chemical safety assessment not required/not conducted 12.6 Other adverse effects An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life. Avoid release to the environment. **13. DISPOSAL CONSIDERATIONS** 13.1 Waste treatment methods Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3089 Class: 4.1 Packing group: II Proper shipping name: Metal powders, flammable, n.o.s. Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No

IMDG

UN number: 3089	Class: 4			acking gro	•		EMS-No: F	G, S-G	
Proper shipping name:	METAL I	POWDER,	FLAMM	ABLE, N.C	.S. (Coppe	er)			
Marine pollutant:yes	. ¹						1.1		 11

ΙΑΤΑ

UN number: 3089	Class: 4.1	Packing group: II
Proper shipping name:	Metal powder,	flammable, n.o.s.

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to	, Section 313: Revision Date	11				
Copper				7440-50-8	2007-07-01	
SARA 311/312 Hazards Fire Hazard, Chronic Health Hazard						
Massachusetts Right To Know Compo	onents					
				CAS-No.	Revision Date	
Copper				7440-50-8	2007-07-01	'
Pennsylvania Right To Know Compon	ents					
				CAS-No.	Revision Date	
Copper		1	:	7440-50-8	2007-07-01	
New Jersey Right To Know Componer	nts					
				CAS-No.	Revision Date	
Copper				7440-50-8	2007-07-01	

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute Aquatic Chronic Flam. Sol. H228	Acute aquatic to Chronic aquatic Flammable solid Flammable solid	toxicity s			 	1 I		 · ·
H400 H412	Very toxic to aqu Harmful to aqua		long lasti	ng effects.	 '	-		 :
HMIS Rating Health hazard: Chronic Health Haz Flammability: Physical Hazard	0 zard: * 3 3			i'	 	:	1 - 1 1	:

NFPA Rating

Health hazard:	0
Fire Hazard:	3
Reactivity Hazard:	 3

Further information

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.

		ef l			, , ,						, , ,	1 - 1 1		
		1 - 1 - 1										:		• •
		}			:		'			'	:		'	:
		al a			1 1 1						1 1 1			
		· · · ·			1 I 1			1 I			1 I 1	11		
				'			'	1	1 I	'				
а – т К		:1			;						;		, e ⁿ	
		· · · ·	; • •		1 I	: • •		1 I	;••		1 I			
	*			*			'	1		'				
r - 1 r		:			ť						ť			
		· · · ·	;**		н н н	: • •		1 I	:		н н н	1 - 1 - 1 1	Page 9	of 9
	*	-	 	*			'	1	· · ·	*		1 - 1 1	'	
	. '	:ť			, , ,			- - -			, , ,	н н н	. '	ľ